



888-786 Discharge Aluminium Hino Mega Truck Air Conditioning Pipeline

Our Product Introduction

for more products please visit us on futureacparts.com

Basic Information

- Place of Origin: China
- Brand Name: Freedom Future
- Model Number: ZS-888-786
- Minimum Order Quantity: Negotiable
- Price: Negotiable
- Packaging Details: standard packing, as customer demands
- Delivery Time: 7 - 15 working Days
- Payment Terms: L/C,T/T,etc.



Product Specification

- Pressure Rating: Up To 300 Psi
- Color: Silver
- Temperature Range: -40°C To 140°C
- Weight: Lightweight
- Oem Part Number: None
- Flexibility: Flexible
- Material: Aluminum
- Resistance: Corrosion Resistant
- Highlight: **Mega Truck Air Conditioning Pipeline,
Hino Mega Truck Air Conditioning Pipeline,
888-786 Discharge Aluminium Pipeline**



Product Description

888-786 Discharge Aluminium Hino Mega Truck Air Conditioning Pipeline

Product Description:

Automobile air conditioning pipes usually adopt a multi-layer structure, including an inner rubber layer, a nylon shielding layer, a middle rubber layer, a polyester fiber reinforcement layer and an outer rubber layer.

This structural design can effectively reduce the permeability of refrigerant and improve the pressure resistance and temperature resistance of the pipeline.

The high-pressure pipe is connected to the condensor to transport the high-temperature and high-pressure refrigerant to the condensor for heat absorption to achieve the cooling effect.



C 型空调软管


Type C Air Conditioner Hose

适合制冷剂 / Applicable refrigerant
R134a, HFO-1234yf

执行标准 / Standard
SAE J2064 QC/T664-2019



工作温度范围
Working temperature range
-40°C ~ +135°C



C 型空调软管尺寸及性能参数

Sizes and performance parameters of type C air conditioner hose

公称直径 Dimension	英寸 Inch	内径 I.D.	外径 O.D.	壁厚 Wall Thickness	壁厚差 Wall Diff	工作压力 Work Pressure	爆破值 Burst Pressure	弯曲半径 Bend Rad	渗透量 Permeability
8.2	5/16"	8.2±0.4	15.2±0.4	3.5	≤0.4	3.5	≥22	75	1.6
10.5	13/32"	10.5±0.4	17.4±0.4	3.5	≤0.4	3.5	≥23	75	1.6
11.2	7/16"	11.2±0.4	18.5±0.4	3.8	≤0.4	3.5	≥23	75	1.6
13.2	1/2"	13.2±0.4	20.8±0.4	3.8	≤0.4	3.5	≥22	85	1.6
15.2	5/8"	15.2±0.4	22.8±0.4	3.8	≤0.4	3.5	≥22	85	1.6
16.0	5/8"	16.0±0.4	23.1±0.5	4.8	≤0.4	3.5	≥22	105	1.6
19.0	3/4"	19.0±0.5	28.5±0.5	5.0	≤0.4	3.5	≥22	110	1.6
22.0	7/8"	22.0±0.5	31.5±0.5	4.8	≤0.4	3.5	≥22	110	1.6
25.0	1"	25±0.5	35.0±0.5	5.0	≤0.4	3.5	≥22	110	1.6

Technical Parameters:

Shape	Bar
Temperature Range	-40-140 Degrees Fahrenheit
Connection Type	Withhold
Durability	Durable
Pressure Rating	200 Psi
Corrosion Resistance	High
Compatibility	Compatible With Most A/C Systems
Color	Silver/Black
Weight	1.4 Lbs
Flexibility	Flexible

Applications:

The application of our automotive air conditioning pipes is not limited to traditional cooling and heating functions, but also includes system integration, environmental protection and energy saving, and technological innovation. These characteristics make the automotive air conditioning pipes improve driving comfort while also meeting the environmental protection and energy saving requirements of modern cars.



COMPANY PROFILE

WE SPECIALISE IN THE A/C HOSES FOR 20 YEARS,

WE ARE GOOD AT MANUFACTURING VARIOUS A/C JOINTS AND A/C PIPES ACCORDING TO DRAWINGS AND PHYSICAL SAMPLES.



120+

WORKER



80+

MACHINE



7000M³

FACTORY

Support and Services:

Our A/C Pipes product technical support team is available to assist you with any questions you may have regarding the installation.

We also offer a variety of services to help ensure the optimal performance of your A/C Pipes, including:

Installation support and guidance

Product testing and analysis

Customization and design services

Our team of experienced professionals is dedicated to providing you with the highest level of customer service and support. Contact us today to learn more about our technical support and services for A/C Pipes.



Ziyou Innovation Trading Co., Ltd.



freedomfuture38@gmail.com



futureacparts.com

Hongyun Auto Parts City, Baiyun District, Guangzhou City, Guangdong Province, China