



888-787 Discharge Aluminium Hino Mega Truck Air Conditioning **Pipeline**

Basic Information

- Place of Origin:
- China Brand Name: Freedom Future ZS-888-787 Model Number: • Minimum Order Quantity: Negotiable • Price: Negotiable • Packaging Details: standard packing, as customer demands • Delivery Time: 7 - 15 working Days
- Payment Terms:





Product Specification

- Pressure Rating:
- Color:
- Temperature Range:
- Weight:
- Oem Part Number:
- Flexibility:
- Material:
- Resistance:
- Highlight:

Up To 300 Psi Silver -40°C To 140°C Lightweight None Flexible Aluminum Corrosion Resistant

Hino Mega Truck Air Conditioning Pipeline, 888-787 Truck Air Conditioning Pipeline



888-787 Discharge Aluminium Hino Mega Truck Air Conditioning Pipeline

Product Description:

Automobile air conditioning pipes usually adopt a multi-layer structure, including an inner rubber layer, a nylon shielding layer, a middle rubber layer, a polyester fiber reinforcement layer and an outer rubber layer.

This structural design can effectively reduce the permeability of refrigerant and improve the pressure resistance and temperature resistance of the pipeline.

Automobile air conditioning pipes are an important part of the air conditioning system, connecting the compressor, condenser, liquid receiver dryer, expansion valve, evaporator and other components to form a closed refrigeration cycle system. Some new air conditioning pipes use polyamide composite materials, which are 50% lighter and 25% cheaper than traditional rubber/aluminum pipe combinations, while reducing the number of crimped connections and the risk of leakage.





C型空调软管尺寸及性能参数

Sizes and performance parameters of type C air conditioner hose

公称直径 Dimension	英寸 Inch	内径 LD.	外径 o.d.	壁厚 Wall Thickness.	壁厚差 Wall Diff	工作压力 Work Pressure	爆破值 Burst Pressure	弯曲半径 Bend Rad	渗透量 Permeability
8.2	5/16"	8.2+0.4	15.2±0.4	3.5	≪0.4	3.5	≥22	75	1.6
10.5	13/32"	10.5+0.4	17.4±0.4	3.5	≪0.4	3.5	≥23	75	1.6
11.2	7/16"	11.2+0.4	18.5±0.4	3.8	≪0.4	3.5	≥23	75	1.6
13.2	1/2"	13.2+0.4	20.8±0.4	3.8	≪0.4	3.5	≥22	85	1.6
15.2	5/8''	15.2+0.4	22.8±0.4	3.8	≪0.4	3.5	≥22	85	1.6
16.0	5/8''	16.0+0.4	23.1±0.5	4.8	≪0.4	3.5	≥22	105	1.6
19.0	3/4"	19.0+0.5	28.5±0.5	5.0	≪0.4	3.5	≥22	110	1.6
22.0	7/8''	22.0+0.5	31.5±0.5	4.8	≪0.4	3.5	≥22	110	1.6
25.0	1"	25+0.5	35.0±0.5	5.0	≤0.4	3.5	≥22	110	1.6

Technical Parameters:

Shape	Bar				
Temperature Range	-40-140 Degrees Fahrenheit				
Connection Type	Withhold				
Durability	Durable				
Pressure Rating	200 Psi				
Corrosion Resistance	High				
Compatibility	Compatible With Most A/C Systems				
Color	Silver/Black				
Weight	1.2 Lbs				
Flexibility	Flexible				

Applications:

The application of our automotive air conditioning pipes is not limited to traditional cooling and heating functions, but also includes system integration, environmental protection and energy saving, and technological innovation. These characteristics make the automotive air conditioning pipes improve driving comfort while also meeting the environmental protection and energy saving requirements of modern cars.



Support and Services:

Our A/C Pipes product technical support team is available to assist you with any questions you may have regarding the installation.

We also offer a variety of services to help ensure the optimal performance of your A/C Pipes, including:

Installation support and guidance

Product testing and analysis

Customization and design services

Our team of experienced professionals is dedicated to providing you with the highest level of customer service and support. Contact us today to learn more about our technical support and services for A/C Pipes.

