

Toyota Corolla 1.3L 88711-12760 Discharge Air Conditioner Pipeline 92-97

Basic Information

. Place of Origin: China

Brand Name: Freedom Future 88711-12760 Model Number: Minimum Order Quantity: Negotiable • Price: Negotiable

Packaging Details: standard packing, as customer demands

. Delivery Time: 7 - 15 working Days

Payment Terms: L/C,T/T,etc.



Product Specification

Material:

. Pressure Rating: Up To 300 Psi Color: Silver And Black -40°C To 140°C • Temperature Range: Lightweight · Weight: 88711-12760 · Oem Part Number: • Flexibility: Flexible Aluminum

Corrosion Resistant Resistance:

• Installation: Easy • Durability: High

• Highlight: 1.3L Discharge Air Conditioner Pipeline,

88711-12760 Discharge Air Conditioner Pipeline

Toyota Corolla Discharge Air Conditioner

Pipeline



Toyota Corolla 1.3L 88711-12760 Discharge Air Conditioner Pipeline 92-97

Product Description:


Multi-layer structure design: Automobile air conditioning hoses usually adopt a multi-layer structure. For example, a five-layer automobile air conditioning hose has an inner rubber layer, a nylon shielding layer, a middle rubber layer, a polyester fiber reinforcement layer, and an outer rubber layer from the inside to the outside. This structural design can prevent seepage layer by layer and effectively reduce the permeability of the refrigerant.

Our company is committed to providing automotive air-conditioning solutions. Automotive cooling nets, automotive expansion valves, and automotive air-conditioning pipes are our company's core products. We believe that cooperating with us can provide you with professional solutions.



C型空调软管 Type C Air Conditioner Hose

适合制冷剂 / Appliable refrigerant R134a,HFO-1234yf



C型空调软管尺寸及性能参数 Sizes and performance parameters of type C air conditioner hose

公称直径 Dimension	英寸 Inch	内径 I.D.	外径 o.b.	壁厚 Wall Thickness.	壁厚差 Wall Diff	工作压力 Work Pressure	爆破值 Burst Pressure	弯曲半径 Bend Rad	渗透量 Permeability
8.2	5/16"	8.2+0.4	15.2±0.4	3.5	≤0.4	3.5	≥22	75	1.6
10.5	13/32"	10.5+0.4	17.4±0.4	3.5	≤0.4	3.5	≥23	75	1.6
11.2	7/16"	11.2+0.4	18.5±0.4	3.8	≪0.4	3.5	≥23	75	1.6
13.2	1/2"	13.2+0.4	20.8±0.4	3.8	≤0.4	3.5	≥22	85	1.6
15.2	5/8"	15.2+0.4	22.8±0.4	3.8	≤0.4	3.5	≥22	85	1.6
16.0	5/8"	16.0+0.4	23.1±0.5	4.8	≤0.4	3.5	≥22	105	1.6
19.0	3/4"	19.0+0.5	28.5±0.5	5.0	≤0.4	3.5	≥22	110	1.6
22.0	7/8"	22.0+0.5	31.5±0.5	4.8	≤0.4	3.5	≥22	110	1.6
25.0	1"	25+0.5	35.0±0.5	5.0	≤0.4	3.5	≥22	110	1.6

Features:

Product Name: A/C Pipes

Temperature Range: -40-140 Degrees Fahrenheit

Color: Silver and Black Connection Type: Withhold Material: Aluminum

Application: Air Conditioning Systems

Keywords: Refrigerant Lines, Tube, AC AIR CONDITIONING PIPE HOSE

Technical Parameters:

Shape	Bar
Temperature Range	-40-140 Degrees Fahrenheit
Connection Type	Withhold
Durability	Durable
Pressure Rating	200 Psi
Corrosion Resistance	High

Compatibility	Compatible With Most A/C Systems
Color	Silver/Black
Weight	1.5 Lbs
Flexibility	Flexible

Application:

Automobile air conditioning pipes can work stably for a long time in the temperature range of -40°C to 140°C, meeting the requirements of refrigerant circulation heat exchange. Suitable for commercial vehicles, passenger cars, off-road vehicles. Automobile air conditioning pipes are used to transport refrigerants to achieve cooling and heating of the air inside the car, providing a comfortable environment for passengers.



Company Profile:

The company's aim is to provide users high quality and effective services. Our products are manufactured according to national standards, industry standards, corporate standards of production and delivery, ISO, DIN, SAE, production and supply of the common international standard.











freedomfuture38@gmail.com



futureacparts.com

Hongyun Auto Parts City, Baiyun District, Guangzhou City, Guangdong Province, China